

Hose Type & Construction

CANVAS FIRE

(cotton & nylon fibre woven flexible U-line inside off-white color rubberised) conforming to IS: 636 Type A

Nominal Bore I.D. in mm	O.D. (mm)	Working Pressure (bar)	Bursting Pressure (bar)	Tolerance in size	Roll Lengths Availability (in meters)
50	56	7	30		30
63	69	7	28		30
75	82	7	25		30
100	107	3.5	15		30

Multistoreyed building, industrial establishments, etc.

SOUJAGE (COUPURE A GAZ FEU DE TOILE)

(Fibre tissé en coton ou nylon en caoutchouc)

LONA FUEGO

(Fibra de algodón y nylon tejen flexible, U-linea dentro color blanco grisáceo de caucho)

LONA A PROVA DE FOGO

(Fibra de algodao e nylon flexivel borracha)

STRAMINFEUER

(gewebte Baumwolle-und Nylonfaser-mit innere flexiblen U-Leitungsnaturweiß, gummiert)

CANVAS VEZELS

(Interne flexibele u-bocht van katoen-en nylon-vezels, gebroken wit, gerubberiseerd)

Врезент огня

(Хлопчаточные и нейлоновые волокна сделаны настольной -лен внутри вне-бело цветный, резиновые)

Heat Resistance - 12 sec. Abrasion Resistance - 200 cycles. Kink Test - 22 Kg/cm²

* brass/gun metal couplings provided, if required on extra charges.

Please forward drawings.

● Colour - off-white



Canvas Fire I.D. (mm) range 38 to 100

w.p. 7 bar

Acieries, des ateliers d'ingé Grattesciel, forestry des unite industriel flexible, revêtement intérieur blanc

Edificio de muchos pisos, sibrultura, establecimiento industrial etc.

Construcoes florestais com muitos andares, florestamento, estabelecimentos industriais etc. mehrstockige Gebäude, Forstwirtschaft, industriellen Anlagen

Flatgebouwen, bosbouw, diverse industriele toepassingen

Многоэтажные здания лесоводство, индустрии и т.д.

TOP SYNTHETIC FIRE FIGHTING

(synthetic nylon fibre woven fungus free flexible inside black color rubberised with synthetic grade rubber) confirming to DIN BS- Type 3

38	50	30
45	50	30
52	50	30
65	50	30
75	50	30
90	40	30
102	40	30

Multistoreyed buildings, forestry, industrial establishment, etc.

Les bâtiments à plusieurs étages les unités industrielles, etc.

Edificio de muchos pisos, establecimiento industrial etc.

● Colour - off-white

LUTTE CONTRE L'INCENDIE SUPERIEUR EN SYNTHETIQUE (Fibre synthétique tissé en nylon flexible revêtu en caoutchouc noir avec caoutchouc de vpe synthétique)

CIMA SINTETICO FUEGO COMBATE

(Sintetica nylon fibra tejen flexible hongo libre dentro calor negro de caucho con caucho grado sintético)

BESTE KUNSTLICHE FEUERBEKAMPFUNG

(gewebte Synthefaser-pilzfrei, flexibel, schwarz, gummiert-mit künstlichem Gummi)

TOP SYNTHETISCHE VUURBESTRIJDING

(Synthetische nylonvezels, schimmelvrij gewoven, voorzien van een flexibele binnenwand, zwart gekleurd, gerubberiseerd met synthetisch rubber)

Верхние синтетическериукавы для огнетушения

(синтетические нейлоновые волокна сливаемые без потанковые стогие внутри чёрноцветные резиновые с синтетический резиной)

**brass/gun metal couplings provided, if required on extra charges.



Top Synthetic Fire Fighting I.D. (mm) range 38 to 102

w.p. 40 to 50 bar

mehrstockige Gebäude, industriellen Anlagen, usw

Flatgebouwen, diverse industriele toepassingen enz.

Многоэтажные здания, промышленности

FIRE RUBBER (FLUTTED/RIBBED)

(synthetic fibre braided with fluted cover) Type III superseeding IS: 444

19	28	12	50	I.D.	25/30/36.5
25	35	12	50	±0.75mm	25/30/36.5
				O.D.	
				±1.0mm	

Fire fighting purposes in multistoreyed buildings.

Lutte contre l'incendie dans dans les grattes-ciels

Fuego combate proposi se edifi cois de muchos pisos Utilizacoes a prove de fogo em prdios com muitos andares.

zur Feuerbekämpfung in mehrstockigen Gebäude Vuurbestrijding in flatgebouwen

Для огнетушения в многоэтажных зданиях

CAOUTCHOUC DE FEU (CANNETE/NERVURE)

(Fibre synthétique tressé avec revêtement cannelé)

FUEGO CAUCHO (REVICIETO/COSTILLA)

(Fibra sintetica galon con flautado cubierta)

BORRACHA A PROVA DE FOGO

(CANELADA/COSTELADA)

(Fibra sintetica trancada com cobertura canelada)

FEUERGUMMI (GERIEFT/VERRIPT)

(beflochtene Synthefaser mit gerieftem Deckel)

WUURRUBBER

(Synthetisch vezel geboord met een gegroefde buitenkant)

Огневая Резина (желобки Ребристые)

(Синтетические волокна с желобком покрывателем)

Temp. - upto 65°C sub. to tol. + 3 mts. per roll length

● Colour - red

